

AKKREDITOITU TESTAUSLABORATORIO*ACCREDITED TESTING LABORATORY***GRANT4COM OY**

Tunnus <i>Code</i>	Laboratorio <i>Laboratory</i>	Osoite <i>Address</i>	www <i>www</i>
T290	Grant4Com Oy	Yrttpellontie 6 90230 OULU <i>Yrttpellontie 6 FI-90230 OULU FINLAND</i>	www.grant4com.fi <i>www.grant4com.fi</i>

Testausalat
Fields of testing

Materiaali- ja tuotetestaus
Material and product testing

PÄTEVYYSALUE SCOPE OF ACCREDITATION		
Testattava materiaali / tuote <i>Material / product tested</i>	Testityyppi, mitta-alue <i>Type of test, measured range</i>	Testausmenetelmä <i>Test method</i>
Materiaali- ja tuotetestaus, Akustiikka <i>Material and product testing, Acoustics</i>		
Koneet ja laitteet <i>Machinery and equipment</i>	Äänentehotason mittaus <i>Measurement of sound power level</i>	ISO 3744:2010 ISO 4871:1996
Koneet ja laitteet <i>Machinery and equipment</i>	Äänenpainetason mittaus <i>Measurement of sound pressure level</i>	ISO 11201:2010 ISO 4871:1996
Materiaali- ja tuotetestaus, EMC/RF-testaus <i>Material and product testing, EMC/RF-testing</i>		
Sähköiset ja elektroniset laitteet <i>Electrical and electronic equipment</i> Radiolaitteet <i>Radio equipment</i> Sähköiset testaus-, mittaus- ja laboratoriolaitteet <i>Electrical equipment for measurement, control and laboratory use</i>	Sähkömagneettinen yhteensopivuus (EMC) <i>ElectroMagnetic Compatibility (EMC) standard for radio equipment and services; Part 1: Common technical requirements</i>	<i>EN 301 489-1</i>
	<i>ElectroMagnetic Compatibility (EMC) standard for radio equipment and services; Part 3: Specific conditions for Short-Range Devices (SRD) operating on frequencies between 9 kHz and 246 GHz</i>	<i>EN 301 489-3</i>
	<i>ElectroMagnetic Compatibility (EMC) standard for radio equipment and services; Part 17: Specific conditions for Broadband Data Transmission Systems</i>	<i>EN 301 489-17</i>

PÄTEVYYSALUE SCOPE OF ACCREDITATION		
Testattava materiaali / tuote <i>Material / product tested</i>	Testityyppi, mittausalue <i>Type of test, measured range</i>	Testausmenetelmä <i>Test method</i>
	<i>ElectroMagnetic Compatibility (EMC) standard for radio equipment and services; Part 19: Specific conditions for Receive Only Mobile Earth Stations (ROMES) operating in the 1,5 GHz band providing data communications and GNSS receivers operating in the RNSS band (ROGNSS) providing positioning, navigation, and timing data</i>	<i>EN 301 489-19</i>
	<i>ElectroMagnetic Compatibility (EMC) standard for radio equipment and services; Part 34: Specific conditions for External Power Supply (EPS) for mobile phones</i>	<i>EN 301 489-34</i>
	<i>Electromagnetic Compatibility (EMC) standard for radio equipment and services; Part 52: Specific conditions for Cellular Communication Mobile and portable (UE) radio and ancillary equipment</i>	<i>EN 301 489-52</i>
	<i>Electromagnetic compatibility (EMC) – Part 3-2: Limits – Limits for harmonic current emissions (equipment input current ≤ 16 A per phase)</i>	<i>IEC/EN 61000-3-2</i>
	<i>Electromagnetic compatibility (EMC) – Part 3-3: Limits – Limitation of voltage changes, voltage fluctuations and flicker in public low-voltage supply systems, for equipment with rated current ≤ 16 A per phase and not subject to conditional connection</i>	<i>IEC/EN 61000-3-3</i>
	<i>Electromagnetic compatibility (EMC) - Part 4-2: Testing and measurement techniques - Electrostatic discharge immunity test</i>	<i>IEC/EN 61000-4-2</i>

PÄTEVYYSALUE SCOPE OF ACCREDITATION		
Testattava materiaali / tuote <i>Material / product tested</i>	Testityyppi, mittausalue <i>Type of test, measured range</i>	Testausmenetelmä <i>Test method</i>
	<i>Electromagnetic compatibility (EMC) - Part 4-3: Testing and measurement techniques - Radiated, radio-frequency, electromagnetic field immunity test</i>	<i>IEC/EN 61000-4-3</i>
	<i>Electromagnetic compatibility (EMC) - Part 4-4: Testing and measurement techniques - Electrical fast transient/burst immunity test</i>	<i>IEC/EN 61000-4-4</i>
	<i>Electromagnetic compatibility (EMC) - Part 4-5: Testing and measurement techniques - Surge immunity test</i>	<i>IEC/EN 61000-4-5</i>
	<i>Electromagnetic compatibility (EMC) - Part 4-6: Testing and measurement techniques - Immunity to conducted disturbances, induced by radio-frequency fields</i>	<i>IEC/EN 61000-4-6</i>
	<i>Electromagnetic compatibility (EMC) - Part 4-8: Testing and measurement techniques - Power frequency magnetic field immunity test</i>	<i>IEC/EN 61000-4-8</i>
	<i>Electromagnetic compatibility (EMC) - Part 4-9: Testing and measurement techniques - Impulse magnetic field immunity test</i>	<i>IEC/EN 61000-4-9</i>
	<i>Electromagnetic compatibility (EMC) - Part 4-11: Testing and measurement techniques - Voltage dips, short interruptions and voltage variations immunity tests</i>	<i>IEC/EN 61000-4-11</i>
	<i>Electromagnetic compatibility (EMC) - Part 6-1: Generic standards - Immunity standard for residential, commercial and light-industrial environments</i>	<i>IEC/EN 61000-6-1</i>

PÄTEVYYSALUE SCOPE OF ACCREDITATION		
Testattava materiaali / tuote <i>Material / product tested</i>	Testityyppi, mittausalue <i>Type of test, measured range</i>	Testausmenetelmä <i>Test method</i>
	<i>Electromagnetic compatibility (EMC) - Part 6-2: Generic standards - Immunity standard for industrial environments</i>	<i>IEC/EN 61000-6-2</i>
	<i>Electromagnetic compatibility (EMC) - Part 6-3: Generic standards - Emission standard for residential, commercial and light-industrial environments</i>	<i>IEC/EN 61000-6-3</i>
	<i>Electromagnetic compatibility (EMC) - Part 6-4: Generic standards - Emission standard for industrial environments</i>	<i>IEC/EN 61000-6-4</i>
	<i>Industrial, scientific and medical (ISM) radio-frequency equipment – Electromagnetic disturbance characteristics – Limits and methods of measurement.</i>	<i>CISPR 11 / EN 55011</i>
	<i>Information technology equipment – Radio disturbance characteristics – Limits and methods of measurement</i>	<i>CISPR 22 / EN 55022</i>
	<i>Information technology equipment - Immunity characteristics - Limits and methods of measurement</i>	<i>CISPR 24 / EN 55024</i>
	<i>Electromagnetic compatibility of multimedia equipment - Emission Requirements</i>	<i>CISPR 32 / EN 55032</i> <i>Exclusions: TVs, set top boxes</i>
	<i>Electromagnetic Compatibility of multimedia equipment – Immunity Requirements</i>	<i>CISPR35 / EN 55035</i> <i>Exclusions: broadcast receivers, CPEs containing xDSL ports</i>
	<i>Electrical equipment for measurement, control and laboratory use - EMC requirements - Part 1: General requirements</i>	<i>IEC/EN 61326-1</i> <i>IEC/EN 61326-2-1</i> <i>IEC/EN 61326-2-2</i> <i>IEC/EN 61326-2-3</i> <i>IEC/EN 61326-2-4</i> <i>IEC/EN 61326-2-5</i>

PÄTEVYYSALUE SCOPE OF ACCREDITATION		
Testattava materiaali / tuote <i>Material / product tested</i>	Testityyppi, mittausalue <i>Type of test, measured range</i>	Testausmenetelmä <i>Test method</i>
	<i>Conformance testing of GSM Terminals (Methods and tests) GSM Frequency bands included: GSM850, GSM900, GSM1800 and GSM1900</i>	<i>3GPP TS 51.010-1 subclauses 12.1 and 12.2</i>
	<i>Electromagnetic compatibility and Radio spectrum Matters (ERM); Short Range Devices (SRD); Radio equipment to be used in the 25 MHz to 1 000 MHz frequency range with power levels ranging up to 500 mW</i>	<i>EN 300 220 (EN 300 330-2, 4.2.2 Unwanted emissions in the spurious domain (EN 300 330-1, 5.9 Unwanted emissions in the spurious domain)</i>
	<i>Wideband transmission systems; Data transmission equipment operating in the 2,4 GHz ISM band and using wide band modulation techniques</i>	<i>EN 300 328 4.3.1.10 Transmitter unwanted emissions in the spurious domain 4.3.1.11 Receiver spurious emission</i>
	<i>Short Range Devices (SRD); Radio equipment in the frequency range 9 kHz to 25 MHz and inductive loop systems in the frequency range 9 kHz to 30 MHz</i>	<i>EN 300 330 4.3.8 Transmitter radiated spurious domain emission limits < 30 MHz 4.3.9 Transmitter radiated spurious domain emission limits > 30 MHz 4. 4.2 Receiver spurious emissions</i>
	<i>Short Range Devices (SRD); Radio equipment to be used in the 1 GHz to 40 GHz frequency range</i>	<i>EN 300 440 4.3.5 Spurious radiations</i>
	<i>Satellite Earth Stations and Systems (SES); Global Navigation Satellite System (GNSS) receivers; Radio equipment operating in the 1 164 MHz to 1 300 MHz and 1 559 MHz to 1 610 MHz frequency bands</i>	<i>EN 303 413 5.5 Receiver spurious emissions test</i>
	<i>Global System for Mobile communications (GSM); Mobile Stations (MS) equipment</i>	<i>ETSI EN 301 511 clauses 5.2.16 and 5.2.17</i>

PÄTEVYYSALUE SCOPE OF ACCREDITATION		
Testattava materiaali / tuote <i>Material / product tested</i>	Testityyppi, mittausalue <i>Type of test, measured range</i>	Testausmenetelmä <i>Test method</i>
	<i>Broadband Radio Access Networks (BRAN); 5 GHz high performance RLAN</i>	<i>ETSI EN 301 893 Radiated Tx and Rx spurious only Restriction: measurement frequency up to 18 GHz</i>
	<i>IMT cellular networks</i>	<i>ETSI EN 301 908-1 Radiated Emissions UE (Devices falling under -2 and -13).</i>
<p>Kun menetelmäviitteessä ei ole versioita (esim. vuosilukua), niin akkreditointi koskee menetelmän viimeisintä versiota/kattaa kaikki voimassa olevat versiot. Tarkka lista menetelmistä on saatavilla laboratorion.</p> <p><i>When version of the test method is not specified accreditation covers all not withdrawn methods / the latest version of the method. Detailed scope is available from the laboratory.</i></p>		